Cordex[™] 650W 48Vdc Modular Rectifier Shelf Systems



Your Power Solutions Partner



- Single shelf modular rectifier solution provides multiple 48V configurations up to 67A for various 48Vdc applications
- > Convection cooled design for high reliability in harsh industrial environments
- > Front access options for space restricted enclosures
- > Integrated DC system capability with controller and distribution module options



Alpha's Cordex series includes a complete range of modular 650W rectifier shelf systems to meet the needs of worldwide telecommunications applications.

Cordex 650W modular shelf systems are available to fit various 48Vdc application needs. 19" rear access solutions are available in a five-module (3.2kW) bulk output version as well as a four-module (2.6kW) integrated solution with an AM plug-in breaker distribution module. Complete front access versions are also available in 23" (4-module) and 19" (3-module) which include a distribution module accommodating both plug-in breakers and GMT fuses. CXCI HP integrated controllers are standard with all 650W shelf systems.

Alpha Cordex 650W rectifier modules feature complete hot-swappability, high efficiency with power factor correction, unique power limiting capability and wide range input. Convection cooling and an ultra compact design also make Cordex shelf systems ideal for the telecommunications industry.





Cordex[™] 650W 48Vdc Modular Rectifier Shelf Systems

CORDEX 48-650W RECTIFIER SHELVES



>19/23in 2RU universal mount

Cordex 2.6kW shelf power system P/N:030-728-20 **Rectifiers:**4 x CXRC 48-650W

Controller:.....1 x CXCI

Distribution:(4) AM bullet type breakers



>19/23in 2RU universal mount

Cordex 3.2kW bulk power system with CXCI controller.

Optional LVD shunt with battery breaker P/N:030-782-20 Rectifiers:5 x CXRC 48-650W

Controller:.....1 x CXCI

Distribution:Bulk power for external distribution

ELECTRICAL

Input voltage (100 to 240VAC model):

Operating: 176 to 320Vac (output power 650W) Extended:176 to 90Vac (derated output power) Operating:100 to 140Vac (output power 500W) Power output:650W at nominal 208 to 240Vac & 500W at nominal 120Vac with 240Vac rectifier

Universal input current: ...3.0 to 3.5A (nominal Vac)

4.9A max. @ 150Vac

100 to 240Vac model:13.5A @ 48Vdc (240Vac)

12A @ 54Vdc (240Vac) 10.4A @ 48Vdc (120Vac) 9.2A @ 54Vdc (120Vac)

MECHANICAL

>19/23" Shelves

Dimensions:

mm:.....89H x 442W x 302D inches:3.5H x 17.4W x 11.9D Weight:................6.5kg (15.5lbs)

Note: Shelf P/Ns DO NOT include modules or distribution breakers Weights DO NOT include modules

Dimensions do not include mounting bracket

Communication ports:

CAN:Interface to control rectifiers Smart peripherals Ethernet:10/100 Base-T for TCIP/SNMP features

ENVIRONMENTAL

Temperature:

Standard:-40 to 50°C (-40 to 122°F) Storage:-40 to 85°C (-40 to 185°F) Humidity:0 to 95% RH non-condensing **Elevation:**....-500 to 3000m (-1640 to 9840ft) Cooling:Natural or forced convection, vertical airflow

AGENCY COMPLIANCE

CSA:.....CSA C22.2 No 60950-1-03 **UL:**.....Std. No 60950-01 CE:.....EN60950



Worldwide Corporate Offices

Headquarter Germany

Hansastrasse 8 D-91126 Schwabach Tel: +49 9122 79889 0 Fax: +49 9122 79889 21 Mail: info@alpha-outback-energy.com

Eastern Europe ee@alpha-outback-energy.com

me@alpha-outback-energy.com

spain@alpha-outback-energy.com

fbnl@alpha-outback-energy.com

France and Benelux

Africa

russia@alpha-outback-energy.com

africa@alpha-outback-energy.com

Alpha and Outback Energy GmbH reserves the right to make changes to the products and information contained in this document without notice. Copyright © 2020 Alpha and Outback Energy GmbH.

Middle East