



High Voltage DC Fuses

System Components and Accessories



Features:

- For use in FLEXware PV combiners with high voltage systems
- DIN rail mount fuse holders with #8 AWG set screw compression terminals
- Touch-safe design, not rated for load make or load break usage

High Voltage DC Fuses Specifications

07/2020

Model	Description	Current Rating	Voltage Rating	Width (in/mm)
OBF-6-600VDC	Fuse	6A	600VDC	—
OBF-10-600VDC	Fuse	10A	600VDC	—
OBF-15-600VDC	Fuse	15A	600VDC	—
OBFH-30-600VDC-DIN	Fuse holder	30A	600VDC	0.7/ 18
FUSE-15-600VDC/10	Carton of (10) fuses	15A	600VDC	—
FH-30-1000VDC-DIN	Fuse holder	30A	1000VDC	0.7/ 18

Preliminary specifications are subject to change.

980-0067-01-00 REV A



Worldwide Corporate Offices

Headquarter Germany

Hansastraße 8
D-91126 Schwabach
Tel: +49 9122 79889 0
Fax: +49 9122 79889 21
Mail: info@alpha-outback-energy.com

Eastern Europe

ee@alpha-outback-energy.com

Middle East

me@alpha-outback-energy.com

France and Benelux

fbnl@alpha-outback-energy.com

Spain

spain@alpha-outback-energy.com

Russia

russia@alpha-outback-energy.com

Africa

africa@alpha-outback-energy.com

Alpha and Outback Energy GmbH reserves the right to make changes to the products and information contained in this document without notice. Copyright © 2020 Alpha and Outback Energy GmbH. All Rights reserved.

For more information please visit www.alpha-outback-energy.com